

glass sheet polarizer	
colorPol[®] VIS 700 BC4 CW02	003528
linear VIS-NIR-polarizer	Date: 22.07.2019


Wavelength range with **contrast > 10 000 : 1**
 (Contrast = ratio of parallel and perpendicular transmittance)
 Transmittance (antireflection coating, 0° incident angle)

600 to 850 nm
 > 84 % up to 93 %

Wavelength range with **contrast > 1 000 : 1**
 Transmittance (antireflection coating, 0° incident angle)

600 to 1000 nm
 > 84 % up to 95 %


Spectral response



Filter thickness

$2,0 \pm 0,2$ mm

Filter size



→ Polarization (electric field vector of transmitted light)

Clear aperture

90 % of surface dimension

Surface imperfections (scratch / dig)

40 / 20 (MIL-O-13830A)

Wavefront distortion (Ø10 mm)

$< \lambda/4$ at 633 nm

Acceptance angle (coating reference for 0°)

$\pm 20^\circ$

Operating temperature

-20 .. +120 °C

CODIXX AG reserves the right to change technical information without notice.

CODIXX AG
 Betrieb Barleben
 Steinfeldstraße 3
 D – 39179 Barleben (Germany)

Phone: +49 39203 963 0
 Fax: +49 39203 963 33
<http://www.codixx.de>
colorPol@codixx.de